

TES-1604 AUTORANGING INSULATION TESTER

RS- Window Version, Data Logger

هایرین مارکت
فروشگاه صنعتی هیرکان



FEATURES

Innovational logging feature (7000) to memorize all of measurements from the work place
RS-232 interface with valued software
4,000M W /V Reding/10,000M W analog indication
Backlight illumination
3-3/4 Digital LCD, 4000Count
Auto Range for Mega Ohm range
50 segments Log Scaled Analog Display
Easy to carry testing package
Tests insulation at rated voltage into a 1mA load
200mA short circuit continuity current
Meet VED0413
Auto discharge



EN61010-1

CAT II pollution 2 1000V

CAT III pollution 2 600V



SPECIFICATION

AC Voltage

Range	Resolution	Accuracy
600V ACV	0.1Volt	1.5%rdg+3dgt (1V~600V)

Continuity

Range	Resolution	Accuracy
40 Ohm (Ish>200mA)	0.01 W	1%rdg+30dgt

Mega Ohm

Range	Resolution	Accuracy
4000M W /250V w/ autorange 4000M/400M/40M/4M	4000M W /250V, 1count/1K W	3%rdg+5Count (under 1G W) 5%rdg+3Count (under 4G W)
4000M W /500V w/ autorange 4000M/400M/40M/4M	4000M W /500V, 1count/1K W	
4000M W /1000V w/ autorange 4000M/400M/40M/4M	4000M W /1000V, 1count/1K W	

GENERAL SPECIFICATIONS

Display	80 x 50mm Big LCD penal with 50 segments analog display Max Reading 4000
Over range Indication	"OL" will be shown on the LCD penal when out of range measurement is made.
Low Battery Indication	The will be shown when the battery need to be changed

Sampling Rate	2.5 times/sec Digital Display 10 times/sec Bar Graph
Power Source	Eight 1.5Volt AA size Battery
Operating Temperature and Humidity	0 °C to 40 °C (32 °F to 104 °F), below 80% RH
Storage Temperature	-10 °C to 60 °C (14 °F to 140 °F)
Dimension	200(L)x140(W)x95(H)mm
Weight	Approx. 900g (with battery)
Accessories	Test Lead, Battery, Instruction Manual, RS-232 interface, Software for Windows .